



WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2	WIRE COLOR
WHITE/ORANGE	1	✕	1	WHITE/ORANGE
ORANGE	2		2	ORANGE
WHITE/GREEN	3	✕	3	WHITE/GREEN
GREEN	6		6	GREEN
BLUE	4	✕	4	BLUE
WHITE/BLUE	5		5	WHITE/BLUE
WHITE/BROWN	7	✕	7	WHITE/BROWN
BROWN	8		8	BROWN
SHEEL		—	SHEEL	

How to order

Cable F/UTP-5E-X-L

X: Color of Jacket + Hood : Standard - Grey
 Optional - Red, Blue, White, Green
 for other color consult sales
 L: Length in metres : Standard - 0,5 / 1,0 / 2,0 / 5,0
 for other length consult sales

NOTE:

- CABLE: F/UTP CAT.5E CABLE, 4P*26WG (7*0.16CCA)
PVC, OD=5.5±0.15MM.
- CONNECTOR: P1 & P2 8P8C PLUG, LONG BODY, GOLD PLATED FU".
- HOOD: MOLDED PVC.
- ELECTRICAL CHARACTERISTICS:
 - NO OPEN, SHORT, MISWIRE AND INTERMITTENCE.
 - 100% ELECTRICAL TEST.
 - INSULATION RESISTANCE: 10M OHMS MIN.
 - CONDUCTOR RESISTANCE: 3 OHMS MAX.
 - HI-POT: DC 300V MIN.

A	INITIAL RELEASE		02/22/16		
REV	DESCRIPTION OF CHANGE		DATE		
TOLERANCE					
.X	.015				.30
.XX	.010				.10
.XXX	.005	.05	SCALE	NONE	
DRAWN BY		UNIT		MM	
CHECK BY		SHEET		1/1	
APPD BY		DATE		04/07/22	
		TITLE:			
		HLD P/N:		Cable F/UTP-5E-X-L	
		CUSTOMER. P/N:			