


(Circuit Diagram)



Notes:

1. Electrical Characteristics:

- 1.1 Contact Resistance: 100mΩ Max
- 1.2 Dielectric Withstanding Voltage: 600V AC(rms) for 1 Minute
- 1.3 Insulation Resistance: 100mΩ Min
- 1.4 Current Rating: 50mA
- 1.5 Voltage Rating: 12V / DC

2. Environment Characteristics:

- 2.1 Storage Temp.: -30°C ~ +100°C
- 2.2 Operate Temp.: -30°C ~ +80°C

3. Others:

- 3.1 Travel: 0.25mm
- 3.2 Life Time: 160gf – 200,000 Cycles
260gf – 100,000 Cycles
- 3.3 Reflow soldering: Max 260°C , 5 seconds

How to Order:

DTSM 6060 - XX - XX (XX XX)

- PL size: standard is 9.0, no Mark
Customer request PL= 8.0 , PL=10.0...
- H size : 4.0 / 4.3 / 4.5 / 5.0 / 5.5 / 6.0 / 6.5 / 7.0 / 8.0 / 9.0 / 10
11/12/13/14/15/16/17/18/19/20/21/22/23/24/25....
- Actuator color: BK - Black / RD - Red / BN - Brown...
- Operation force: 160gf / 260gf / 320gf

■ Standard packing is Tape and Reel

SCHMID-M

GENERAL TOLERANCE

X* ± 5.0°	X. ± 0.30
.X* ± 3.0°	.X ± 0.25
.XX* ± 2.0°	.XX ± 0.15
.XXX* ± 1.0°	.XXX ± 0.10

DESIGN: Johnson

DATE: 2022.01.18

DWG. NO.:

TITLE:

CHECK: Vanda

DATE: 2022.01.19

DTSM 6060

6 * 6 Tact Swich , SMD type

REV.: 01	UNIT.: mm	SCALE.: 1:1	PAGE.: 1/1
----------	-----------	-------------	------------

AUDIT:
APPROVE:

DATE: 2022.01.19
DATE: 2022.01.19