



Tolerance of Cutting Tilt

1	Pitch (P)	1.0	5	Strip Length (S)	5.0 Ref.	9	Conductor Width (Cw)	0.7 ± 0.03
2	Margin Width (M)	1.0	6	Support tape Length (d)	10.0 Ref.	10	Conductor Thickness (Ct)	0.05 ± 0.01
3	Total Pitch (Pt)	$1.0 \times (\text{Pin} - 1)$	7	Terminal thickness (t)	$0.29 \sim 0.34$	11	UL Style 20706	
4	Total Width (W)	$1.0 \times (\text{Pin} + 1)$	8	Total Length (L)	See the table	12	All the BOM of FFC are RoHs compliant	

<p>RoHS Compliant</p> <p>SCHMID-M</p>		<p>TOLERANCE</p> <p>XX ± 0.25</p> <p>XX ± 0.35</p> <p>ANG. ±</p>		<p>PART NAME</p> <p>Flat Flexible Cables, 1mm, Type 1, 20 Pin, 150 mm</p>	
<p>APPD.</p>	<p>SCAIF</p>	<p>UNIT</p> <p>MM</p>	<p>SIZE.</p> <p>A 4</p>	<p>PART NO.</p> <p>SM C01 0805 20</p>	
<p>DWG.</p> <p>HELGA</p>	<p>PAGE</p> <p>1 OF 1</p>	<p>REV.</p> <p>C</p>			
<p>DATE</p> <p>2013/10</p>					