



Circuit	Dimension		Q'TY /Tube
	A	B	
04	8.45	2.54	69pcs
06	10.99	5.08	53pcs
08	13.53	7.62	43pcs
10	16.07	10.16	36pcs
12	18.61	12.70	31pcs
14	21.15	15.24	27pcs
16	23.69	17.78	24pcs
18	26.23	20.32	22pcs
20	28.77	22.86	20pcs
22	31.31	25.40	17pcs
24	33.85	27.94	14pcs
26	36.39	30.48	11pcs



NOTES:
 Rating Current: 1.0AMP
 Withstand Voltage: 500V AC/DC
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Operation Temperature: -40°C to +105°C

Contact Material: Phosphor Bronze
 Contact Plating: Sn over Ni
 Insulator Material: High Temperature plastic (UL94V-0)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC
 TOLERANCES ARE:
 DECIMALS Angle
 XX: ±0.40 ± 3°
 XXX: ±0.25
 XXXX: ±0.15

PART NO: SM C02 3135g XX B

TITLE: MicroMatch IDC Box W/polarization XX:Nr. Positions

SCALE 1:1
 UNIT MM
 PROJ.
 SHEET

A0	2015/06/25	NEW	Hua.ZT		Hua.ZT
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE