



Specification:
 Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 1000M Ohm Min. At 500VDC.
 Rated Voltage And Current: 1.5A At 250VAC Minimum.
 Dielectric Withstanding Voltage:
 750V AC (rms) for 1 Minute(Rev. 1.1)
 Durability (Life Test): 1500 Cycles
 Insertion Force: 35 Newton Maximum.
 Extraction Force: 10 Newton Minimum.

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	PBT G.F. (UL94V-0)	WHITE		1
2	PIN TERM.	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	Gold(1~3u"); Ni(40~60u"); TD(120u") (100% pure Tin of lead free plating)	4
3	SHELL	BRASS T:0.3	NICKEL PLATED	NI(80~120u")	1

RoHS
Compliant

SCHMID-M

APPD.
SCALE
UNIT
DATE
2012/9/12
M M
PAGE
1 OF 1

TOLERANCE
X ± 0.38
Y ± 0.25
Z ± 0.13
XXX ± 0.05
SIZE
A 4
REV.
B

PART NAME
USB B TYPE DIP TYPE 4P FEMALE 90° HORIZONTAL
NICKEL SHELL SELECTIVE GOLD PLATING
WHITE COLOR ROHS

PART NO.
SM C04 8317 04 BFH