



| | | |
|----------------------|---|--------------------|
| Standard | UL | VDE |
| Rated voltage | 300V | 320V |
| Rated current | 15A | 20A |
| Wire range | 28-12AWG | 2.5mm ² |
| Withstanding voltage | AC2500V/1Min | |
| Ambient temperature | (-)40°C to +105°C | |
| Strip length | 7mm | |
| Torque | 0.4Nm(3.5Lb-In.) | |
| Pitch | 5.08mm | |
| Poles | 2P, 3P ---Any poles | |
| Housing | PA66, UL94V-0 | |
| Screws | M2.5, steel, Cr ³⁺ Zn plated | |
| Wire Cage | Brass, Ni plated | |
| Contact Cage | Brass, Ni plated | |



| | | | |
|----------------|-------------|---|---|
| RoHS Compliant | | SCHMID-M | |
| APPD. | SCAIF | TOLERANCE XX ± 0.25 XX ± 0.35 ANG. ± | PART NAME Pluggable Terminal Block Wire to Wire Without Fix Screws Pitch 5,08 mm Green XX: No. Poles |
| DWG. HELGA | UNIT M M | SIZE. A 4 | PART NO. SM C09 05812 XX WOC |
| DATE 2013/10 | PAGE 1 OF 1 | REV. C | |