



Standard	UL	VDE
Rated voltage	300V	320V
Rated current	15A	20A
Wire range	24-12AWG	0,2-3,3mm ²
Withstanding voltage	AC2500V/1Min	
Ambient temperature	(-)40°C to +105°C	
Strip length	7mm	
Torque	0.4Nm(3.5Lb-In.)	
Pitch	5.08mm(.197")	
Poles	2P, 3P ---Any poles	
Housing	PA66, UL94V-0	
Screws	M2.5, steel, Cr ³ + Zn plated	
Wire Cage	Brass, Ni plated	
Contact Cage	Brass, Ni plated	



APPD. DWG. Brawn DATE 2019/04		SCALE UNIT M M PAGE 1 OF 1	TOLERANCE XX ± 0.25 XX ± 0.35 ANG. ± SIZE. A 4 REV. C	PART NAME Pluggable Terminal Block Wire to Wire Mounted Screw Pitch 5,08 mm Green XX: No. Poles PART NO. SM C09 05817k XX WMC
-------------------------------------	--	----------------------------------	--	--

linear dimension(Tolerances Standard GB/T 14486-2008)										
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	over 100 to	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

RoHS Compliant

SCHMID-M