



P=7.62mm, (N for hole digits), (Significant Digits): 02P~24P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	14.62	22.24	29.86	37.48	45.10	52.72	60.34	67.96	75.58	83.20	90.82	98.44
B	7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	
L	106.06	113.68	121.30	128.92	136.54	144.16	151.78	159.40	167.02	174.64	182.26	
B	99.06	106.68	114.30	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	

UL	IEC
300V/16A	400V/20A
28~12AWG	0.2~2.5mm ²
AC 2500V	
6000V	
DC500V 5COMΩ above	
≤8nΩ	
7mm	
-40°C~+105°C	

Housing: PAL66 (UL94 V-0)
 Contact: Copper alloy, Ni plated
 Screws: Steel, Zn plated
 Cage: Copper alloy, Ni plated

TOLERANCE				
SCALE	UNIT mm			
DRAW	Walter	DATE	5.4.2019	TITLE SM C09 0763 XX SOC
CHECK	Vanda	REV		
		DESCRIPTION Pluggable Terminal Block RM7,62mm		