



| | | |
|----------------------|-------------------------------------|---------------------|
| Standard | UL | VDE |
| Rated voltage | 300V | 750V |
| Rated current | 52A | 57A |
| Wire range | 20-6AWG | 10.0mm ² |
| Withstanding voltage | AC3000V/1Min | |
| Ambient temperature | -40°C~+105°C | |
| Strip length | 4.5mm | |
| Torque | 1.2Nm(10.5Lb-In.) | |
| Pitch | 10.16 mm(.197") | |
| Poles | 2P , 3P ---Any poles | |
| Housing | PA66,UL94V-0 | |
| Screws | M4,steel,Cr ³⁺ Zn plated | |
| Solder Pins | Brass, Tin plated | |
| Contact Cage | Brass, Ni plated | |

| | | | |
|---------------------------------------|----------------------------------|--|--|
| | | | |
| APPD. DWG. GRAY DATE 2014/01/30 | SCALE UNIT M M PAGE 1 OF 1 | TOLERANCE 0 ± .00 ± ANG. ± SIZE. A 4 REV. A | PART NAME Terminal Block, Screw Clamp Style, Hor. cond., Pitch 10,16mm, PCB Straight, XX..... Nr. Pins PART NO. SM C09 11630 XX SS4 |