



Specifications:

Electrical:

- 1.Current Rating 1.5A/contact terminal
- 2.Voltage Rating :30V DC
- 3.Contact Resistance:30 milliohms MAX
- 4.Dielectnic Withstanding Voitage:500 V AC AT Sea Level
- 5.Insulation Resistance:1000MEGA ohms MIN

Mechanical:

- 1.Connector Mate and Unmate Force:
Mate force:3.75kgf(MAX)
Unmate force:0.40kgf(MIN)
- 2.Terminal Retention :0.40kgf(MIN)

Material:

- 1.Housing:
Hing Temperature Tnermaplastics,
UI 94V-0 LCP White/Black
- 2.Contact:Copper Alloy C2680
- 3.Shell: Copper Alloy C2680/SPCC

Finish:

- 1.Contact: Plated Gold in Mating Area; Tin On Solder Talls
- 2.Shell: Nickel Plating

TOLERANCE		SCHMID-M
SCALE	UNIT mm	
DRAW Walter	DATE 5.5.2013	TITLE
CHECK Vanda	REV	SM C04 8331 05 BF
		DESCRIPTION
		MINI USB(1.1) B a*t1 TYPE SP .t FEMALE P.C.B SMT STRAIGHT TYPE SELECTIVE GOLD PLATI NG PLASTIC POLARIZING PEGS 6.0mm BLACK INSUL.